

SopORTE

Para cojinete de roscar

SopORTE de cojinete de roscar



A4 4600

Para Ø de cojinete x altura mm A4 4600	Rosca						Longitud total mm
	Métrica	Métrica fina	Whitworth	Tubo Whitworth	UNC	UNF	
16x5	M 1-M 2,6	M 1x0,2-M 2,6x0,35	1/16-3/32"	---	n.º 1-n.º 4	n.º 0-n.º 4	160
20x5	M 3-M 4	M 3x0,25-M 6x0,5	1/8"	---	n.º 5	n.º 5-n.º 6	180
20x7	M 4,5-M 6	M 5x0,75-M 6x0,75	5/32-1/4"	---	n.º 6-1/4"	n.º 8-1/4"	180
25x9	M 7-M 9	M 7x0,5-M 9x1	5/16"	---	5/16"	5/16"	210
30x11	M 10-M 11	M 10x0,75-M 11x1	3/8-7/16"	G 1/8"	3/8-7/16"	3/8-7/16"	270
38x10	---	M 12x1-M 15x1	---	G 1/4"	---	1/2-9/16"	310
38x14	M 12-M 14	---	1/2-9/16"	---	1/2-9/16"	---	310
45x14	---	M 16x1-M 20x2	---	G 3/8-G1/2"	---	5/8-3/4"	440
45x18	M 16-M 20	---	5/8-3/4"	---	5/8-3/4"	---	440
55x16	---	M 22x1-M 26x1,5	---	G 5/8-G 3/4"	---	7/8-1"	500
55x22	M 22-M 24	---	7/8-1"	---	7/8-1"	---	500
65x18	---	M 27x1,5-M 36x2	---	G 7/8-G1"	---	1.1/8-1.3/8"	560
65x25	M 27-M 36	M 30x3-M 36x3	1.1/8-1.3/8"	---	1.1/8-1.3/8"	---	560